Dynamic CCTVLtd Quality, Reliability, Price

iVMS 4200 CMS

Specifications

Model		iVMS-4200				
Operating System		Microsoft Windows 7/Windows 2008 (32/64bit) Windows 8/81 (32/64bit) Windows 2003/Windows XP(32bit) Windows 10				
Client	User	Up to 51 users supported				
	Encoding Device	Up to 256 encoding devices supported				
	Group	Up to 256 groups supported				
	Channel	Up to 64 channels can be imported to each group; Up to 1024 channels can be imported to all groups				
	Storage Server	Up to 16 storage servers supported				
	Stream Media Server	Up to 16 stream media servers supported				
	Decoding Device	Up to 64 decoding devices supported				
	Live View	Up to 64-ch live view supported at a time				
	Auxiliary Screen Preview	Up to 3 auxiliary screens supported for preview				
	Playback	Up to 16-ch playback supported at a time; Up to 16-ch synchronous playback supported				
	E-map	Up to 256 E-maps can be added				
	Hot Region	Up to 255 hot regions can be added				
	Hot Spot	Up to 64 camera hot spots can be added; Up to 64 alarm input hot spots can be added				
	PTZ Control	Up to 256 presets / 1 pattern / 16 patterns can be added; Each patrol supports up to 32 presets				
	Download	Up to 16-ch downloading supported at a time				
Storage Server	User	Up to 32 users supported				
	Record Performance	Up to 64-ch x2Mbps supported at a time				
	VOD Performance	Up to 64-ch x2Mbps supported at a time				
	iVMS-4200 Client	No limit for the amount of iVMS-4200 connected to the storage server				
Steam Media Server	Input/output stream	Up to 64-ch input video stream supported; Up to 200-ch output video stream supported				

Recommended Configurations

PC Configuration Bitrate (single P-frame)	The maximum amount of accesses supported for live view channel					
	CPU: Intel Core i7-3770K 3.50GHz Memory: 4GB Graphic card: AMD Radeon HD 6700 Series Operating System: Windows 7 (32 bit)	CPU: Intel Core i5-2320K 3.00GHz Memory: 46 Graphic card: NVIDIA GeForce GT 430 Operating System: Windows 7 (32 bit)	CPU: AMD Phenom II X4 965 3.40GHZ Memory: 4G Graphic card: ATI Radeon HD 5770 Series Operating System: Windows XP SP3	CPU: Intel Core 2 Quad Q8200 2.33GHZ Memory: 4G Graphic card: NVIDIA GeForce 9600GT Operating System: Windows XP SP3	CPU: Intel Core 2 Duo E8400 3.00GHZ Memory: 2G Graphic card: ATI Radeon HD 4800 Series Operating System: Windows XP SP3	
(352*288)*768K*25	64	64	64	63	48	
(640*480)*1.5M*25	57	50	48	25	22	
(704*576)*2M*25	49	38	36	19	17	
(960*576)*2M*25	36	26	27	12	12	
(1280*720)*6M*25	23	18	16	8	7	
(1280*960)*6M*25	20	15	13	6	5	
(1600*1200)*8M*25	12	8	8	3	3	
(1920*1080)*9M*25	12	7	7	3	3	
(2048*1536)*13M*25	8	6	6	2	2	
(2560*1920)*7M*6	6	6	6	5	4	

Note: The parameters recommended above are for reference only