

# TFT 19" Pro



TFT 19"/PRO is the latest in a new series of displays from iiyama is the Prolite, a 19" LCD display designed for demanding CCTV and Broadcast Applications. The new 19" CCTV Display Features a fast 5 m/s response time and a 1000:1 contrast ratio offering great colour performance with clear and vivid images. BNC and VGA inputs to ensure compatibility across multiple platforms, and VESA compliance allows for easy installation in any surveillance and security environment.

**FEATURES:**

- Ultra high resolution 600 TV lines for the PAL version \***
- Superior image quality**
- High contrast ratio 1000:1**
- Fast response time 5ms**
- Support up to 1280 x 1024 resolution**
- Height adjustable and swivelling stand for desktop**
- Built-in speakers**
- Support vesa(R)-compliant mounting solution**

**TFT 19"/PRO**

General	
Panel	TN
Diagonal	19"
Display area	h x w 301.01 x 376.32 mm; 11.85" x 14.8"
Response time	5 ms
Contrast	1000 : 1 typical
Brightness	300 cd/m <sup>2</sup> typical
Viewing zone	horizontal/vertical: 170°/160°; right/left: 85°/85°; up/down: 80°/80°
Display colour	16.7 million
Aspect ratio	5 : 4
Pixel pitch h x v	0.294 x 0.294 mm
Inputs	D-Sub, AV (BNC), Audio, S-Video
Output connector	AV (BNC), Audio, S-Video
Native resolution	1280 x 1024 (1.3 megapixel)
Horizontal sync	30 - 82 KHz
Vertical sync	56 - 75 Hz
Synchronization	Separate Sync
Plug & Play	VESA DDC2B™
Feature	
Speakers	2 x 1 W (Stereo)
Included accessories	power cable, D-Sub cable, stand, quick start guide
Controls	On-Screen-Display in 8 languages (EN, FR, DE, IT, ES, PT, NL, SE) and 5 Front controls (Power, InputSelect/ Select, Scroll up, Scroll down, Meu/ Exit) User controls picture PC input (auto adjust, contrast, temperature, H. position, V. position, clock, phase), picture AV, S-Video input (contrast, brightness, tint, colour, sharpness, flesh tone, colour temperature), sound (volume, bass, treble, balance, mute), option (source, OSD language, OSD H.position, OSD V.position, duration, reset, video mode)
Ergonomics	Energy Star®
Safety	CE, TUV/Bauart
Power supply	
Power supply	AC 100 - 240 V, 50 / 60 Hz
Power Supply Unit	internal
Power usage	35 W typical
Anti-theft-device	Kensington-lock™ prepared
VESA mounting	100 mm
Tilt angle	20° up; 5° down
Dimensions w x h x d	407 x 431.5 x 200.5 mm
Weight	5 kg

**Dimensions Units mm (inch)**

