

Testmonitor4”

The monitor has been designed as one complete unit doing away with any awkward fly leads and loose battery packs, it offers a 4” colour LCD screen with analogue side controls and audio as standard, the unit is small and compact and comes in a stylish leather carry case which is equipped with velcro attachment straps and sun visor.



Model	Testmonitor4”
Display	4”Color TFT LCD
Number of dots	480 (W) x 234 (H)
Display Area	82.11(W) x 61.77(H)
Dot Pitch	0.171(W) x 0.264(H)
Color Configurations	R.G.B delta
Back Light	LED
Input Signal	NTSC &PAL (auto-switch) composite video signal 1.0 Vp-p/75 ohm. Negative. Audio: 150~250 mVp-p / 1.0
Input/Output Terminal	VIDEO: BNC. Auto Termination. AUDIO: RCA Jack
Lamp Life-time	10,000hr min. (at Temp=25°C)
Viewing Angle (min)	U/D/L/R 10/30/45/45
Brightness	250 nit (typ.)
Contrast Ratio	150:1 typical
Response Time	Tr: 15ms Tf: 20ms (Typ)
Power Voltage	1.2Volts x 6 (Size “AA”) 2200mAH Rechargeable battery
Power Consumption	3.0 W max
Operating Temperature	0°-60°
Storage Temperature	-20°-80°
Operating Humidity	Max.85%RH
Storage Humidity	Max.85%RH
Dimension (mm)	152(W) x105.6 (H) x38.6 (D)
Weight	320g(w/o Battery)
External Control	Volume, Brightness, Color