

iDS-7700NXI-I4/16P/16S(B) DeepinMind SERIES NVR



Features and Functions

Human and Vehicle Analysis

Deep learning-based human and vehicle target classification improves false alarm filtering effect

Professional and Reliable

- New logical and visualized GUI design
- Dual-OS design to ensure high reliability of system running
- ANR technology to enhance the storage reliability when the network is disconnected

Video Input and Transmission

- Full channel IP cameras connection
- Connectable to the third-party network cameras

Compression and Recording

- H.265+ compression effectively reduces the storage space and costs by up to 75%
- Full channel recording at up to 12MP resolution

HD Video Output

- HDMI and VGA independent outputs provided
- HDMI Video output at up to 4K resolution

Storage and Playback

- Up to 4 SATA interfaces for HDD connection
- 16-ch synchronous playback at up to 1080p resolution
- Normal/Important/Custom video playback
- Files management
- HDD health monitoring

Smart & POS Function

- Supports multiple VCA (Video Content Analytics) events
- Smart search for the selected area in the video; and smart playback to improve the playback efficiency
- POS information overlay on live view and playback
- POS triggered recording and alarm

Network & Ethernet Access

- Hik-Connect for easy network management
- Gigabit Ethernet network interface
- 16 independent PoE network interfaces are provided




Specifications

Model		iDS-7716NXI-I4/16P/16S(B)	iDS-7732NXI-I4/16P/16S(B)
Human/Vehicle analysis	False alarm filtering	Up to 16-ch 2 MP video analysis for human and vehicle recognition to filter false alarm	
Video/Audio input	IP video input	16-ch	32-ch
		Up to 12 MP resolution	
	Two-way audio	1-ch, RCA (2.0 Vp-p, 1 k Ω)	
Network	Incoming bandwidth	320 Mbps	
	Outgoing bandwidth	256 Mbps	
	Remote connection	128	
Video/Audio output	Recording resolution	12 MP/8 MP/6 MP/5 MP/4 MP/3MP/1080p/UXGA/720p/VGA /4CIF/DCIF/2CIF/CIF/QCIF	
	CVBS output	1-ch, BNC (1.0 Vp-p, 75 Ω), resolution: PAL: 704 × 576, NTSC: 704 × 480	
	HDMI1 output resolution	4K (3840 × 2160)/60Hz, 4K (3840 × 2160)/30Hz, 2K (2560×1440) /60Hz, 1920 × 1080p/60Hz, 1600 × 1200/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz	
	VGA output resolution	2K (2560×1440) /60Hz, 1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz, HDMI1/VGA Simultaneous Output	
	HDMI2 output resolution	1920×1080/60Hz, 1280×1024/60Hz, 1280×720/60Hz, 1024×768/60Hz	
	Audio output	1-ch, RCA (Linear, 1 kΩ)	
Decoding	Decoding format	H.265/H.265+/H.264/H.264+/MPEG4	
	Live view / Playback resolution	12 MP/8 MP/6 MP/5 MP/4 MP/3MP/1080p/UXGA/720p/VGA /4CIF/DCIF/2CIF/CIF/QCIF	
	Synchronous playback	16-ch	
	Capability	16-ch @ 1080p	
Network management	Network protocols	TCP/IP, DHCP, Hik-Connect, DNS, DDNS, NTP, SADP, SMTP, NFS, iSCSI, UPnP™, HTTPS	
Hard disk	SATA	4 SATA interfaces	
	Capacity	Up to 8 TB capacity for each HDD	
	eSATA	1 eSATA interface	
External interface	Network interface	1, RJ-45 10/100/1000 Mbps self-adaptive Ethernet interface	
	Serial interface	RS-485 (half-duplex), RS-232, Keyboard	
	USB interface	Front panel: 2 × USB 2.0; Rear panel: 1 × USB 3.0	
	Alarm in/out	8/4	
PoE interface	Interface	16 RJ-45 10/100 Mbps self-adaptive Ethernet interfaces	
	Power	≤ 200W	
	Supported standard	IEEE 802.3 af/at	
General	Power supply	100 to 240 VAC	

Total power	≤ 350 W
Consumption (without hard disk)	≤ 30 W
Working temperature	-10 °C to 55 °C (14 °F to 131 °F)
Working humidity	10 to 90 %
Chassis	19-inch rack-mounted 1.5U chassis
Dimensions (W × D × H)	445 × 400 × 71 mm (17.5" × 15.7" × 2.8")
Weight (without hard disk)	≤ 5 kg (11 lb)

Physical Interfaces



Index	Description	Index	Description
1	LAN Interfaces	2	AUDIO OUT
3	AUDIO IN	4	HDMI Interface
5	USB 3.0 Interface	6	RS-232 Serial Interface
7	VGA Output (DB9 Connector)	8	RS-485 Serial Interface
9	Controller Port, Alarm In/Alarm Out	10	GND
11	100 to 240 VAC power supply	12	Power Switch
13	Network Interfaces with PoE function	14	eSATA Interface
15	VIDEO OUT		

Available Models

iDS-7716NXI-I4/16P/16S(B), iDS-7732NXI-I4/16P/16S(B)

Distributed by



Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
overseasbusiness@hikvision.com

Hikvision USA
T +1-909-895-0400
sales.usa@hikvision.com

Hikvision Italy
T +39-0438-6902
info.it@hikvision.com

Hikvision Singapore
T +65-6684-4718
sg@hikvision.com

Hikvision Africa
T +27 (10) 0351172
sale.africa@hikvision.com

Hikvision Europe
T +31-23-55-42-770
info.eu@hikvision.com

Hikvision France
T +33(0)1-85-330-450
info.fr@hikvision.com

Hikvision Oceania
T +61-2-8599-4233
salesau@hikvision.com

Hikvision Hong Kong
T +852-2151-1761

Hikvision Middle East
T +971-4-8816086
salesme@hikvision.com

Hikvision Spain
T +34-91-737-16-55
info.es@hikvision.com

Hikvision Canada
T +1-909-895-0400
sales.usa@hikvision.com

Hikvision Russia
T +7-495-669-67-99
saleru@hikvision.com

Hikvision Poland
T +48-22-460-01-50
poland@hikvision.com

Hikvision Korea
T +82-31-731-8841
sales.korea@hikvision.com

Hikvision India
T +91-22-28469900
sales@pramahikvision.com

Hikvision UK
T +01628-902140
support.uk@hikvision.com

Hikvision Brazil
T +55 11 3318-0050
Latam.support@hikvision.com