



32" LED MONITOR

DS32-4KLED

32" LED Monitor

DS32-4KLED

Panel Type	LED
Case Type	Plastic
Maximum Resolution	3840 (H) x 2160 (V)
MTBF	50,000 hrs
Active Display Area	698 × 392 (H×V)
Pixel Pitch	0.181 × 0.158 (H×V) mm
Bezel Thickness	Left / Right / Top 20mm, Bottom 30mm
Contrast Ratio	1000 : 1
Brightness	300 cd / m ²
Response Time	5m.sec (G to G)
Viewing Angle	178 / 178° (H/V)
Display Colours	1.07B (10-bit)
Video Synchronisation	Yes
PC Compatibility	Yes
Aspect Ratio	16:9 / 4:3
VGA Auto Frequency Correction	N/A
Speakers	0
Sound Demodulation	No
Mute	Yes
Work Humidity	5% - 90%
Work Temperature	0 - 40 °C
Volume +/- Power On/Off	Yes



IN / OUT INTERFACE

Video Interface	1 x HDMI v2.0 input, 2 x HDMI v1.4 input, 1 x DP v1.2 input
Audio	1 x Output
Termination	N/A
Certification	CE, FCC, ROHS
VESA	100 x 100
Stand Type	Desk
Colour	Black
Button Position	Back bottom right
Monitor Packing Dimensions	792mm x 134mm x 548mm
Packing Dimensions	800mm x 270mm x 550mm
Gross Weight	11.2kgs

POWER

Power Supply	220 / 240 AC
Power Consumption	50 Watt
Voltage:	12 v DC
Power Interface	DC 12V in x 1

OSD CONTROLS

Contrast, Brightness, DCR, Saturation, OSD position, Gamma, Color temp, Hue, Low blue light, Sharpness, Noise reduction, Aspect Ratio, Mute, Volume, Multi-Window, OSD position

OSD LANGUAGE

English, French, Russian, Spanish, German, Italian, Portuguese, Turkish, Danish, Polish and Dutch

ACCESSORIES

Power cord, Adapter, Stand, User's guide, HDMI cable, Remote control

