

DS-TCL400-E(2.8mm)

Hikvision

IP pole-mounted camera

SOLUTIONS range


4 MPx (2688x1520)

2.8 mm Lens

License Plate Recognition | Traffic

Control

Smart LED light



Hikvision

SOLUTIONS range

ANPR IP camera on pole

1/1.8" Progressive Scan CMOS

4 Megapixel (2688x1520)

2.8 mm Lens

Minimum illumination 0.04 Lux @ (F2.0, AGC ON)

Compression H.265 / H.264

License plate recognition

Traffic control

2 x RJ-45 10/100/1000M BaseT

PoE IEEE802.3af

WEB, CMS, Smartphone and NVR interface

ONVIF Compatible

Weatherproof IP67

Specifications

Brand	HIKVISION
Range	SOLUTIONS
Image sensor	1/1.8" Progressive Scan CMOS
Maximum resolution	4 Megapixel (2688x1520)
Compression	H.265 / H.264
Bitrate	32 Kbps - 16 Mbps
Lens	2.8 mm
Minimum illumination	Colour: 0.04 Lux @ (F2.0, AGC ON) Black and White: 0.02 Lux @ (F2.0, AGC ON)
Infrared lighting	No
Shutter time	1-30/100,000 s
Day / Night	Automatic
Image improvements	BLC, HLC, 3D-DNR, AGC, AWB
License plate recognition	Yes
Intelligent functions	Supports vehicle entry and exit detection
Internal memory	No
Network interface	2 x RJ-45 10/100/1000M BaseT
Communication	1 x RS-485
Remote access	Web Browser, Hik-Connect Smartphone App, PC Software iVMS-4200 and Hik-Central
Interoperability	ONVIF, ISAPI
Power	DC 12-24 V PoE IEEE802.3af
Degree of protection	Weatherproof IP67
Dimensions	Ø base 160 mm x 917.5 mm (H) x 114.3 mm (W)
Base dimensions	Ø base 160 mm / Ø entre tornillos 128 mm / 3 ranuras para ajuste
Weight	2 kg