



ALL RACK 24 PORT CAT6 PATCH PANEL

NOTES:

ELECTRICAL:

1. VOLTAGE RATING:125 VAC RMS
2. CURRENT RATING:1.5AMP
3. CONTACT RESISTANCE:100MILLIOHMS MAX
4. INSULATION RESISTANCE:1000 MEGOHMS MIN @500 VDC
5. DIELECTRIC STRENGTH:750 VAC RMS 60Hz, 1MIN

ENVIRONMENTAL:

1. STORAGE:-40° TO +85°
2. OPERATION:0° TO 70°

MECHANICAL:

1. HOUSINGG MATERIAL:ABS;
2. PANEL FRAME:CARBON STEEL, POWDER, COATING IN BLACK COLOR, Spcc1.5mm;
3. PCB MATERIAL:FR-4 T=1.6mm ;
4. IDC MATERIAL:PC , CONTACT:PHOSPHOR BRONZE; WITH NICKEL PATING ;
5. RJ45 JACK LIFE:750 TIMES MIN;
6. IDC LIFE:200 TIMES MIN;
7. WIRE:AWG 22-26;

Material				Item No.	PNL24ABCAT6	
Angles Projection	Size	Scale	Unit	Part Name	24Ports Cat6 UTP Patch Panel	
	A4	X:1	mm	Tolerance		
Sheet	1 OF 1	Version:	A/0	0.00-20.00	±0.10	
				20.00-50.00	±0.15	
				50.00-100.00	±0.20	
				100.00-	±0.25	
				Angle	±30'	