

# RG-RAP6260(H)-D

Reyee

AP Directional Wi-Fi 6 High Density

Frequency 2.4 and 5 GHz / 160MHz

Channel Width

Supports 802.11a/b/g/n/ac/ax

Transmission speed up to 6000 Mbps

MU-MIMO antennas 4x4 in 2.4GHz,

4x4 in 5GHz



Reyee

Wifi access point 6 802.11ax dual-band 2,4 and 5 GHz

Compatible with 802.11a/b/g/n/ac/ax

Allows connections up to 6000 Mbps

Antennas with MIMO technology 4x4 2.4GHz and 4x4 5GHz

2.4GHz Directional antennas: 50°H x 30°V and 5GHz: 60°H x 30°V

Channel width up to 160MHz

1 Ethernet Ports 2,5G MultiGigabit

1 Gigabit SFP Port

Temperature range from -40 to 65 °C

Hi-PoE power supply 802.3bt

# Specifications

<b>Brand</b>	Reyee
<b>Wireless standard</b>	Wi-Fi 6 802.11ax
<b>Frequencies</b>	2.4GHz & 5GHz
<b>Wi-Fi performance</b>	Up to 6000Mbps Radius 1: 2.4GHz Up to 1148 Mbps Radius 2: 5GHz Up to 4804 Mbps
<b>Integrated antenna</b>	Internal antennas 2.4GHz MU-MIMO 4x4 Directional 50°H x 30°V Internal antennas 5GHz MU-MIMO 4x4 Directional 60°H x 30°V
<b>SSID</b>	Up to 8
<b>Operating modes</b>	Wireless access point Routing with basic functions Compatible with Reyee AP Mesh
<b>Security</b>	WPA / WPA2 (AES) / WPA-PSK
<b>Management</b>	Configuration via web or remote interface with Ruijie Cloud
<b>Interface</b>	1 Port RJ45 10/100/1000/2500 Mbps 1 SFP port 10/100/1000 Mbps
<b>Power</b>	Jack 48Vdc Hi-PoE 802.3bt 40W
<b>Operating temperature</b>	-40°C ~ 65 °C
<b>Dimensions</b>	300 x 300 x 75,5 mm (Without mounting kit)
<b>Weight</b>	3,5 Kg (excluding mounting kit)