

**SFX/OSP1-61-LSZH-GRY**

OSP1-61 1pr 22AWG Overall Foil Screen 600V Grey LSZH (8761)



<b>Cable Construction</b>	1 Pair
Conductor	Tinned Copper
Conductor Diameter (mm)	0.24 ±0.008 x 7
Stranded Diameter (mm)	0.76
<b>Insulation</b>	HDPE
Insulation Thickness (mm)	0.430
Insulation Diameter (mm)	1.55 ±0.10
Insulation Colours	Black, Clear
<b>Al-PET Shield</b>	>=115%
<b>Drain Wire</b>	
Conductor	Tinned Copper
Conductor Diameter (mm)	0.24 ±0.008 x 7
<b>Jacket</b>	LSZH
Jacket Thickness (mm)	0.60
Overall Diameter (mm)	4.40 ±0.20
Jacket Colour	Grey RAL 7042
Sheath Printing	OSP1-61 2x22AWG 600V Overall Screened LSZH RoHS2 (PO) (m)
Reaction to Fire	Eca
<b>Electrical Characteristics</b>	
Max Conductor DC resistance @ 20°C	<56.00Ω/km
Rated Temperature	70°C
Rated Voltage	600V
Insulation Resistance @20°C	>200MΩ/km