## ЛЛХ

Superior product line

## CombiProtect S Jeweller

Wireless motion and glass break detector.



PD 6662 2017 SOON SSF SOON NFA2P

2


GRADE


What's new

Baseline CombiProtect Jeweller	Superior CombiProtect S Jeweller
SmartBracket mounting panel without holding screw	SmartBracket mounting panel with holding screw
Common battery	Enhanced battery
Glossy enclosure	Matte enclosure
Available for all PROs	Available only for accredited partners

This is the device of the **Superior product line**. Superior products are advanced versions of Jeweller devices. This product line is developed for projects. Only accredited Ajax Systems partners can sell, install, and administer Superior products.








- SmartDetect algorithm to prevent false alarms
- Temperature compensation
- Pet immunity





- DualTone two-factor glass break verification algorithm: by low and high frequencies
- Filter for false alarms caused by dog barking or truck-passing sounds



- Up to 1,200 m of radio communication in an open space
- Data is encrypted throughout the transmission process
- Regular polling to display current device statuses



- Tamper alarm
- Device authentication to prevent spoofing
- Jamming detection
- Holding screw to secure the device on SmartBracket





- Up to 5 years of battery life
- Low battery notifications
- Panasonic pre-installed battery

- Pairing with a hub via QR code
- Remote control and configuration in the app
- Effortless installation and replacement

Superior, Fibra, and Baseline product lines are mutually compatible. This opens up numerous possibilities for building systems of any configuration.

Compliance with standards	Communication with control panel	Motion detection	Glass break detection
EN 50131-2-2 (Grade 2) EN 50131-2-7-1 PD 6662:2017 SSF (coming soon)	Jeweller communication technology Frequency bands	Sensitive element 1 × PIR sensor Detection distance	Sensitive elements 1 × electret microphone Glass break detection distance
NFA2P (coming soon)	868,0 – 868,6 MHz	up to 12 m	up to 9 m
Compatibility	<b>Communication range</b> up to 1,200 m	Motion detection angles horizontal — 88.5°	Horizontal glass break detection angle
Hub Plus, Hub 2 (2G), Hub 2 (4G), Hub 2 Plus, Hub Hybrid (2G), Hub Hybrid (4G)	In an open space	<b>Pet immunity</b> weight: up to 20 kg height: up to 50 cm	180°
<b>Range extenders</b> ReX, ReX 2			
Power supply	Installation	Enclosure	Complete set
Battery 1 × CR123A	<b>Operating temperature range</b> from -10°C to +40°C	<b>Colour</b> white, black	CombiProtect S Jeweller 1 × CR123A battery (pre-installed)

Battery life	Operating humidity	Dimensions	SmartBracket with holding screw
up to 5 years	up to 75%	110 × 65 × 50 mm	Installation kit
			Quick start guide
Manufacturer	Protection class	Weight	
Panasonic	IP50	92 g	



For detailed information, scan the QR code or follow the link:

ajax.systems/support/devices/combiprotect-s/

support@ajax.systems

- @AjaxSystemsSupport\_Bot
- ajax.systems