

AMAX

DOUBLEBUTTON



Wireless double panic button for fast response



To activate the alarm, you must simultaneously press both buttons. They are stiff and parted by a plastic barrier. These measures eliminate false alarms when carrying DoubleButton in a pocket or bag.

DoubleButton supports confirmed alarms. This feature implies instructing users: what sequence of presses is required to generate a confirmed alarm condition. It gives a 100% guarantee that a hold-up alarm was raised intentionally and only by an authorized user.



Specification

Classification	Wireless hold-up device
Compatibility	Operates with Ajax Hubs and range extenders featuring OS Malevich 2.10)
False alarm prevention	Yes
Number of buttons	2
Alarm transmission	Not longer than 0,15 sec Always active (does not require waking up to use)
Jeweller radio tech	Communication range with a hub - up to 1300m in an open area Two way communication channel Operating frequencies - 868.0 - 868.6 or 868.7 - 869.2MHz Self-adjusting RF output power - up to 20 mW Block encryption based on AES algorithm Frequency hopping
Power supply	Battery: Cr2032 battery Battery life - up to 5 years
Operating temp range	From -10°C to +40°C
Permissible humidity	Up to 75%
Protection class	IP55
Size	47 x 35 x 16mm
Weight	17g
Complete set	DoubleButton Pre-installed Cr2032 battery Quick start guides