

WEATHERPROOF EXIT BUTTON



WP-EBSS25/PTE

SPECIFICATION

WP-EBSS25

- · Contacts: Double pole N/O N/C
- Output: 4 AMP contact @ 30V AC/DC
- Wear resistant legend
- External use
- Rated IP65 ingress protection
- Silver contacts
- Operating temperature -20° to +60°c
- Operating travel: 2mm
- · Contact resistance: 10m OHM (Max)
- Operating life (mechanical): 1,000,000

FEATURES

WP-EBSS25

- Stainless Steel Button
- Momentary operation / contact
- High impact plastic back box
- Surface fitting
- Easy clean surface
- · Ideal for general / sensitive areas
- \cdot Gasket and gland included
- Screw footprint for flush fitting onto standard back box
- Distance between fixing holes 60mm

200 C

OTHER PRODUCTS

EPS/PTE

AH600

ML600

JMB/KS-1

PRESS

TO EXIT

3

DIMENSIONS

WP-EBSS25

- 85H x 85W x 40/50D (mm)
- · 248g (Boxed)
- · 200g (Unboxed)



- WP-EBSS25
- Stainless Steel Exit Button
- · Stainless Steel Plate (2mm)
- 2 Security Screws
- Allen Key
- \cdot Surface Box
- Gland
- \cdot Gasket





