



The Hikvision DS-7332HWI-SH is a 32 channel analogue DVR offering the latest 960h recording at realtime 25fps. This DVR has fantastic image quality coupled to an excellent use of web functions with the ability to be used across multiple devices such as Windows and Mac along with fantastic support through Apps for iPhone and Android mobile phones.

FEATURES:

- **H.264** video compression
- **Up to 32-ch** video input
- **960h (PAL:960x576)** resolution real-time recording
- **HDMI and VGA** output at up to **1920x1080P** resolution
- **Dual-stream**
- **Gigabit network** interfaces
- **16-ch** synchronous playback
- **HDD** quota and group management
- **Push notification**
- **DVD/RW** (optional)



Dimensions Unit: mm (inch)

DS-7332HWI-SH	
VIDEO/AUDIO INPUT	
Video Compression	H.264
Video Input	32-ch
Video Input Interface	BNC (1.0Vp-p, 75Ω), PAL
Audio Compression	G.711u
Audio Input	16-ch, RCA (2.0 Vp-p, 1kΩ)
Two-way Audio Input	1-ch, RCA (2.0 Vp-p, 1Ω) [using the audio input]
VIDEO/AUDIO OUTPUT	
HDMI/ VGA Output	1080P:1920 x 1080 /60 Hz; SXGA: 1280 x 1024 /60 Hz; 720P:1280 x 720 /60 Hz; XGA: 1024 x 768 /60 Hz.
Spot Output	1-ch, BNC (1.0 Vp-p, 75 Ω)
Encoding Resolution	WD1/4CIF/2CIF/QCIF
Frame Rate	25fps
Video Bit Rate	32 Kbps ~ 3072 Kbps, or user defined (max. 3072 Kbps)
Audio Output	2-ch, RCA (linear, 600Ω)
Audio Bit Rate	64 Kbps
Dual-Stream	Support; sub-stream: CIF / QCIF @ 25 fps
Stream Type	Channel1-4: Video, Video & Audio; Other channels: Video
Synchronous Playback	16-ch
HARD DISK	
SATA	4 SATA interface
Capacity	up to 4TB capacity for each disk
EXTERNAL INTERFACE	
Network Interface	1, RJ45 10M / 100M Ethernet interface
Serial Interface	1 RS-232, RS-485 (half-duplex), Keyboard
USB Interface	3, USB2.0
GENERAL	
Power Supply	12 VDC
Consumption	≤ 40W
Working Temperature	-10°C ~ +55°C
Working Humidity	10% ~ 90%
Chassis	19-inch rack-mounted 1.5 U chassis
Dimensions (WxHxD)	445 x 70 x 390mm (17.51" x 2.75" x 15.35")
Weight	≤ 5kg (without hard disk)

