


HIKVISION DS-2CD2732F-IS VANDAL RESISTANT IP DOME CAMERAS OUT OF BOX IMAGE AND VIDEO STREAMING SETTINGS.

The below settings are default out of the box for the above IP dome camera and can be customized by the user or installer from the web front end of the camera or through the iVMS 4200 remote management software if required.

Display and DSP settings

Display Settings



Brightness	<input type="range" value="50"/>	50
Contrast	<input type="range" value="50"/>	50
Saturation	<input type="range" value="50"/>	50
Hue	<input type="range" value="50"/>	50
Sharpness	<input type="range" value="50"/>	50
Iris Mode	Auto	▼
Smart IR	Disable	▼
Exposure Time	1/25	▼
Video Standard	50hz	▼
Day/Night Switch	Auto	▼
Sensitivity	Normal	▼
Switch Time	<input type="range" value="5"/>	5
Mirror	Close	▼
WDR	Close	▼
BLC Area	Close	▼
White Balance	AWB1	▼
Digital Noise Reduction	Normal Mode	▼
Noise Reduction Level	<input type="range" value="50"/>	50
Scene Mode	Outdoor	▼
Local Output	Enable	▼

Video network streaming settings

Video **Audio**

Stream Type	Main Stream(Normal)	▼
Video Type	Video&Audio	▼
Resolution	1920*1080P	▼
Bitrate Type	Constant	▼
Video Quality	Highest	▼
Frame Rate	25	▼
Max. Bitrate	8192	Kbps
Video Encoding	H.264	▼
I Frame Interval	50	

HIKVISION DS-2CD2732F-IS VANDAL RESISTANT IP DOME CAMERAS OUT OF BOX IMAGE AND VIDEO STREAMING SETTINGS.

Sub Stream

Video	Audio
Stream Type	Sub Stream
Video Type	Video&Audio
Resolution	352*288
Bitrate Type	Variable
Video Quality	Medium
Frame Rate	25
Max. Bitrate	512 Kbps
Video Encoding	H.264
I Frame Interval	50